

IK-KV-11.6W

IK-KV-11.6W Flat Panel Display

New! IK-KV-11.6w is our newest rugged LCD touch-screen display, at 11.6? wide. It is a high-bright, daylight readable flat panel display with a two-point capacitive touch screen and integrated speakers. *The night mode feature allows for a quick transition from lowest brightness to highest brightness to accommodate day vs. night setting.* Connect to this display with a S9/S10 Samung phone with the Samsung Dex. You can also connect your Samsung Tablet directly to the 11.6? iKey Display with a single cable. Resolution: 1920(RGB) x 1080. Fully mountable, IK-KV-11.6 is ideal for vehicle mount and most public safety vehicles. VESA Mounting Pattern: 6-32 Threaded Inserts in 75mm x 75mm Pattern. Features:

- Two-Point Capacitive Touch Screen
- 3 USB Type A ports, 1 USB 3.0 Type A upstream port
- Video input: HDMI or USB-C
- Power supply: 12VDC
- Color: Black
- Night mode
- Temperature Range: Operating 0°;C to 50°;C, Storage: -20°;C to 60°;C
- Mounting: VESA 75mm x 75mm pattern

Please download the "Info Sheet" in the downloads section for all specs and photos.

Check out our new video.

Product Code IK-KV-11.6W

| LCD SIZE | 11.6" |
|--------------|---------------------------------|
| RESOLUTION | 1920 x 1080 |
| DISPLAY MODE | Normally black |
| POWER | 12 VDC |
| INPUT | MONITOR: HDMI, TOUCHSCREEN: USB |



iKey

| BUTTON FUNCTIONS | Power, Menu, Volume Up/Down, Brightness Up/Down, Night Mode, Blackout |
|-------------------|---|
| TEMPERATURE RANGE | STORAGE: -4F to +140F (-20C to 60C) OPERATING: 32F to +122F (0C to 50C) |
| PIXEL ARRANGEMENT | RGB Vertical Stripe |
| THERMAL SHOCK | Should be able to withstand 6 cycles. (1 cycle: -20/30min change interval~ +60 C/ 30 min, 5 min change interval |
| MOUNTING PATTERN | VESA 75mm x 75mm |
| HUMIDITY | 10-90% (No Condensation) |
| WEIGHT | 3.0 lbs |
| Dimensions | 11.71"x 8.21"x 1.36" (I-w-d) 297.1mm x 208.5mm x 34.5mm |